

Part Number: 9535

RS-232, #24-5c, SR-PVC, O/A Foil, PVC Jkt, CMG

## **Product Description**

Computer EIA RS-232 Cable, 24 AWG stranded (7x32) tinned copper conductors, semi-rigid PVC insulation, overall Beldfoil® shield (100% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

# **Technical Specifications**

# **Physical Characteristics (Overall)**

Condu	ctor		
AWG	Stranding	Material	No. of Conductors
24	7x32	TC - Tinned Copper	5
Condu	ictor Count:		
Conductor Size:			

#### Insulation

Material	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.01 in

### **Color Chart**

Number	Color
1	Black
2	White
3	Red
4	Green
5	Brown

### **Outer Shield Material**

Тур	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Тар	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	7x32 mm

### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.189 in	0.032 in

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
25 Ohm/1000ft	18 Ohm/1000ft

#### Capacitance

- apaonano			
Nom. Capacitance Conductor to Conductor		Nom. Capacitance Conductor to Other Conductor to Shield	
33 pF/ft		65 pF/ft	
Shielding:			Foil(s) or Copper Tape(s)

### Current

Max. Recommended Current [A] 1.75 Amps per conductor @ 25°C A

## Voltage



### **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2464)
Operating Temp Range:	-30°C To +80°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	22 lbs/1000ft
Max Recommended Pulling Tension:	27.5 lbs
Min Bend Radius/Minor Axis:	2 in

#### **Standards**

NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	2464 (300 V 80°C)
CPR Euroclass:	Eca

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	No	
---------------	----	--

### **Part Number**

# Variants

Item #	Color	Footnote
9535.0030	Chrome	
9535.00U305	Chrome	
9535.01152	Chrome	
9535.01305	Chrome	
9535 060100	Chrome	
9535 0601000	Chrome	С
9535 060500	Chrome	С
9535 0605000	Chrome	С
9535 060U1000	Chrome	
9535 060U500	Chrome	

Footnote: C - CRATE REEL PUT-UP.

### © 2018 Belden, Inc

# All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.