

## ETD Cores (9595444502)



Part Number: 9595444502

95 ETD CORE SET

ETD cores have been designed to make optimum use of a given volume of ferrite material for maximum throughput power, specifically for forward converter transformers. The structure, which includes a round center post, approaches a nearly uniform cross- sectional area throughout the core and provides a winding area that minimizes winding losses. ETD cores are used mainly in switched- mode power supplies and permit off- line designs where IEC and VDE isolation requirements must be met.

□ETD cores can be supplied with the center post gapped to a mechanical dimension or an A<sub>1</sub> value.

Weight indicated is per pair or set.

Weight: 94 (g)

VV CISII	<u>ı.</u> 27 (8)	<u>'</u>			<u></u>
Dim	mm	mm tol	nominal inch	inch misc.	
A	44	± 0.75	1.732	_	Chart Legend  Σl/ A : Core Constant, l <sub>e</sub> : Effective Path  Length, A <sub>e</sub> : Effective Cross- Sectional Area,  Effective Core Volume
В	22.3	± 0.20	0.878		
C	14.8	± 0.35	0.583		
D	16.5	± 0.20	0.65	_	
Е	32.5	min	1.28	min	
F	14.8	± 0.35	0.583	_	
$A_L$ :		tance Fact			
Expla	nation c	of Part Nur	mbers: Digits 1 & 2	= product class a	nd 3 & 4 = material grade.

Electrical Properties				
$A_L(nH)$	5100 ±25%			
Ae(cm <sup>2</sup> )	1.73			
$\Sigma l/A(cm^{-1})$	6			
l <sub>e</sub> (cm)	10.35			
$V_e(cm^3)$	17.94			
$A_{min}(cm^2)$	1.717			

A<sub>1</sub> value is measured at 1 kHz, B < 10 gauss

Fair- Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288

www.fair- rite.com

888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair- rite.com