


Description



United States of America

Designed for dry packaging Surface Mount Devices. Monitors the most critical humidity range for SMD's. Color reference bar assists with accurate readings.

Standards

inside the bag.

Complies with EIA 581, MIL-P-116, and MIL-I-8835.

Specifications

Materials: Blotting paper impregnated with cobaltous chloride.

Accuracy: Based on ambient temperature of 75°F.

Tolerance: Approx. 2.5% for each 10°F away from 75°F.

Part Number	Card Size	Std Package	Relative Humidity
4HIC100	2" x 3"	100 pieces / can	10/20/30/40

RoHS 2, REACH, and Conflict Minerals Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2014/12/17, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See SCS Warranty, Limitation of Liability and Remedies

Specifications and procedures subject to change without notice.

A SPOT HUMIDITY INDICATOR CARD 400/CAN

	4-SPOT HOWIDTT INDICATOR CARD 100/CAN			
SCS	926 JR Industrial Drive, Sanford, NC 27332 WEB SITE: StaticControl.com PHONE (919) 718-0000	DRAWING NUMBER 4HIC100	DATE May 2015	